


Substrate Notes: It is manufactured as smooth and woodgrain sheets consisting of wood fibres bound with natural lignin. Weathertex is a highly durable exterior grade hard board used for the cladding of residential and commercial buildings. It is 97% timber and 3% natural wax with no glues, resins or formaldehydes. In its natural un-primed form, it comes with a 10 year guarantee from the manufacturer.

Substrate Preparation Notes: Ensure the Natural (unprimed) Weathertex is thoroughly clean and dry before commencing. If there is any doubt, measure moisture content which must be less than 15% before staining or finishing can commence. Examine the surface for the presence of grease, oil, wax, tannin, building marks, or other contaminants. Soap and water may be used where appropriate, then left to dry.


Coating System Summary

Preparation Coat Simply Woodcare Wood Cleaner

<p>Coating Application Details</p> 	<ul style="list-style-type: none"> • Shake container thoroughly before use. • Wear rubber gloves, covered footwear and safety glasses during use. • If cleaning near gardens and metal surfaces hose down prior to cleaning and again after completion. • All surfaces must be clean, dry and free of wax, grease and other contaminants • Wet the surface thoroughly with water. For best results let the surface soak for at least 30 minutes. • Clean the surface thoroughly with Simply Woodcare Exterior Wood Cleaner mixing 1 part wood cleaner with 3 parts water in a plastic container. Avoid contact with metal. • Apply generously and scrub thoroughly. • Allow to stand for 10-15 minutes and rinse surface thoroughly using a garden hose (note: do not use a pressure washer). • For heavily discoloured or greyed areas a repeat application may be required. • Ensure all traces of wood cleaner are removed prior to application of any finishing coats. • Allow the surface to dry for at least 24 hours prior to application of finishing products. • For further information, download the data sheet from the Haymes website
---	--

Finishing Coat Haymes Simply Woodcare Dexpress

1st Coat: SDEX	Haymes Simply Woodcare Dexpress Stain
2nd Coat: SDEX	Haymes Simply Woodcare Dexpress Stain
Optional: SDEX	Haymes Simply Woodcare Dexpress Stain
Recommended for optimum performance and extreme exposure conditions	

<p>Coating Application Details</p> 	<ul style="list-style-type: none"> • Do not apply if ambient temperature is less than 10°C or greater than 30°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to thinning advice. • Do not apply if rain is expected within 24 hours. • Do not apply to hot surfaces, or in direct sunlight. • Stir thoroughly before and during application using a broad flat stirrer. • Apply two coats by brush. Dexpress may also be applied on broad wall areas with a 10-12mm synthetic roller and laid off with a brush to provide best results. Apply along the length of the board including all exposed edges and end grain. • For further information, please download the data sheet from the Haymes website
<p>CARE & MAINTENANCE</p>	<p>Protect the coating from abrasive contact for seven days. Periodically cleaning the surface with a mild detergent or Simply Woodcare Wood Cleaner will rejuvenate the surface and extend the service life by removing contaminants which can damage the surface. It is important to reapply Dexpress when the coating begins to show signs of wear.</p>